## LPC-P215W-LPx

21.5" Stainless Steel P-cap Panel PC with Intel 7th/6th Gen KabyLake-U/Skylake-U Core™ i7/i5/i3, 6 sides IP66 Waterproof Feature and Wide Range Power Input



## / Features

- York / Desk / Vesa Mounting
- > 21.5" P-cap Flat Bezel
- DC 12~24V Wide Range Power Input
- 1920\*1080 Resolution
- Bottom Side M12 Plastic Connector
- M12 Plastic Waterproof Connectors
- Stainless Steel 316 Food Grade



System				
Processor	7th/6th Gen KabyLake	7th/6th Gen KabyLake-U/Skylake-U Core™ i7/i5/i3		
System Memory DDR4 2133MHz SO-DI		•		
External I/O Port	1 x GIGA LAN Externa (the end side is male F 1 x USB 2.0 External W (the end side is female 1 x Power External Wa (the end side is 2 wire	<ul> <li>1 x GIGA LAN External Waterproof cables by 1.5 meters</li> <li>(the end side is male RJ45)</li> <li>1 x USB 2.0 External Waterproof cables by 1.5 meters</li> <li>(the end side is female USB 2.0)</li> <li>1 x Power External Waterproof cables by 1.5 meters</li> <li>(the end side is 2 wire : ground &amp; + )</li> <li>1 x COM (1 x RS-232/422/485) External Waterproof cables by 1.5 meters</li> </ul>		
Storage	2 x SATA3 (6.0Gb/s) 1 x mSATA (full size m	ini-PCle)	-PCle)	
Operating System	, i i i i i i i i i i i i i i i i i i i	,	xy Lake-ULT Only)Windows 8.1 (64bit)	
Expansion	2 x MiniPCIe Slot			
LCD		Environment		
Display Type	21.5" TFT LCD	Operating Temp	-20~60 °C,IEC-60068-2-1/2/14	
Max. Resolution	1920*1080	Storage Temp	-20~60 °C	
Max. Color	16.7M	Humidity	10~90% @40 °C, non-condensing	
Luminance	250nits	EMC	FCC / CE Class A Certification	
View Angle 89/89/89/89			CE Class B Compliant	
Backlight Lifetime	30,000 hours	Vibration	1.5 Grms @10~500Hz, IEC-60068-2-64	

Power Requirement		Mechanical	
Power Input	M12 Power Input	Construction	Stainless Steel case
	DC 12~24V Wide Range	IP Rating	IP66 with 6 sides
	Power Input	Mounting	VESA
Touch Screen		Dimension	TBC
			•

Type 21.5" P-cap USB interface

Ordering Information				
LPC-P215W-LP5	21.5" Stainless Steel P-cap Panel PC with Intel Skylake-U i3-6100U,			
	6 sides IP66, and Waterproof M12 Plastic Connector			
LPC-P215W-LP6	21.5" Stainless Steel P-cap Panel PC with Intel Skylake-U i5-6300U,			
	6 sides IP66, and Waterproof M12 Plastic Connector			
LPC-P215W-LPK3	21.5" Stainless Steel P-cap Panel PC with Intel Kabylake-U i3-7100U,			
	6 sides IP66, and Waterproof M12 Plastic Connector			
LPC-P215W-LPK5	21.5" Stainless Steel P-cap Panel PC with Intel Kabylake-U i5-7300U,			
	6 sides IP66, and Waterproof M12 Plastic Connector			
WFK-024	WiFi kits w/ cable & Antenna (2.4GHz, 802.11 b/g/n, 1T1R)			
WFK-524	WiFi kits w/ cable & Antenna (2.4 & 5GHz, 802.11 a/b/g/n/ac + BT, 2T2R)			
04-US-26-00002	120 W / 24V power adapter with 3 pin terminal block (For High Brightness Model)			
Ordening Code				
Ordering Code				
LPC-P215W-LPx Series -H / -OB / -B / -AG / -AR / -V / -M				
H = High Brightness 1000 nits LED backlight				
OB = Optical Bonding				

B = Glass Withtout Touch

AG = Anti-Glare

AR = Anti-Reflection

V = Vandal Proof Glass (By Project)

M = M12 Metal Connector

